

**Certification
Issued Under the Authority of the
Federal Communications Commission
By:**

**Bay Area Compliance Laboratory Corp.
1274 Anvilwood Avenue
Sunnyvale, CA 94089**

**Date of Grant: 09/08/2017
Application Dated: 09/08/2017**

**High-Flying Electronics Technology Co., Ltd.
Room 1002, Building 1, No.3000, Longdong Avenue,
Pudong New Area,
Shanghai, 201203
China**

Attention: Sen Xie , General Manager

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: 2ACSV-HF-LPT230
Name of Grantee: High-Flying Electronics Technology Co., Ltd.
Equipment Class: Digital Transmission System
Notes: Wi-Fi Module
Modular Type: Single Modular

| <u>Grant Notes</u> | <u>FCC Rule Parts</u> | <u>Frequency Range (MHZ)</u> | <u>Output Watts</u> | <u>Frequency Tolerance</u> | <u>Emission Designator</u> |
|--------------------|-----------------------|------------------------------|---------------------|----------------------------|----------------------------|
| | 15C | 2412.0 - 2462.0 | 0.039 | | |

Modular Approval. Output power listed is conducted. This transmitter is approved for use in Mobile RF exposure category configurations with the antenna(s) installed to provide a separation distance of at least 20 cm from all persons. This grant is valid only when the module is sold to OEM or OEM integrators. The antenna(s) used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter except in accordance with FCC multi-transmitter product procedures. End-users must be provided with specific information required to satisfy RF exposure compliance for final host devices and installations. Compliance of this device in all final host configurations is the responsibility of the Grantee. Installation of this device into portable RF Exposure category host devices requires the submission of a Class II permissive change or new application. The device supports 20 MHz and 40 MHz bandwidth modes.

